

ABRIDGEMENT

A swinging pinion on the side of an upper swing structure is meshed with a ring gear which is provided on and around the inner periphery of an inner ring on the side of a vehicular base carrier. A grease bath is provided on the inner side of the inner ring and under a swing frame. A center joint is located in an opening which is provided in the swing frame at the center of swinging motions of the upper swing structure. The grease bath is formed by bath-forming walls around an central top plateau wall which is connected the center joint on the inner peripheral side. An annular seal member of resilient material is interposed between the top plateau wall of the grease bath and the lower side of the swing frame. The annular seal member is formed in a height which is larger than the width of spacing between the top plateau wall and the swing frame. At one side, the seal member is detachably fixed either on the side of the swing frame or on the side of the top plateau wall section. At the other side, the seal member is provided with an annular sliding portion which is held in sliding contact with the other one of the swing frame and the top plateau wall in an inclined posture in a radially inward direction.

506972

(12)特許協力条約に基づいて公開された国際出願

08 SEP 2004

(19) 世界知的所有権機関
国際事務局(43) 国際公開日
2004 年 4 月 22 日 (22.04.2004)

PCT


(10) 国際公開番号
WO 2004/033805 A1

- (51) 国際特許分類⁷: E02F 9/12, F16J 15/32 (72) 発明者; および
(21) 国際出願番号: PCT/JP2003/013056 (75) 発明者/出願人 (米国についてのみ): 星 暁生 (HOSHI, Akio) [JP/JP]; 〒315-0055 茨城県 新治郡 千代田町稲吉南2-4-1 筑波寮 Ibaraki (JP). 田村 和久 (TAMURA, Kazuhisa) [JP/JP]; 〒315-0017 茨城県 石岡市 若宮 4-2-2 Ibaraki (JP). 田中 望 (TANAKA, Nozomu) [JP/JP]; 〒300-0028 茨城県 土浦市 おおつ野 7-3-13 Ibaraki (JP). 田畑 修司 (TABATA, Shuuji) [JP/JP]; 〒315-0051 茨城県 新治郡 千代田町新治 1828-3 千代田ハウス 4-305 Ibaraki (JP). 川崎 浩二 (KAWASAKI, Koji) [JP/JP]; 〒300-0501 茨城県 稲敷郡 江戸崎町鳩崎 349 Ibaraki (JP). 柳沢 幸男 (YANAGISAWA, Yukio) [JP/JP]; 〒300-0023 茨城県 土浦市 沖宿町 747 Ibaraki (JP).
- (22) 国際出願日: 2003 年 10 月 10 日 (10.10.2003)
- (25) 国際出願の言語: 日本語
- (26) 国際公開の言語: 日本語
- (30) 優先権データ:
特願 2002-298331
2002 年 10 月 11 日 (11.10.2002) JP
- (71) 出願人 (米国を除く全ての指定国について): 日立建設株式会社 (HITACHI CONSTRUCTION MACHINERY CO., LTD) [JP/JP]; 〒112-0004 東京都 文京区 後楽二丁目 5 番 1 号 Tokyo (JP).

[続葉有]

(54) Title: ROTATING APPARATUS FOR CONSTRUCTION MACHINE

(54) 発明の名称: 建設機械の旋回装置



(57) **Abstract:** In a rotating apparatus, a ring gear with which a rotating pinion provided on an upper rotation body meshes is provided on the inner periphery of an inner ring on the lower traveling body side. A grease bath is formed in the inner side of the inner ring. A center joint is installed in an opening formed at the position of rotation center of the upper rotation body. The center joint is connected to a connection wall extended from a bath forming wall of the grease bath. A sealing member for sealing the grease bath is provided at a position between the upper face of the connection wall and the lower face of a frame of the upper rotation body, and the position is more toward the outer periphery side than the installation portion of the center joint. The sealing member is a circular elastic member and has a height dimension larger than the space between the connection wall and the frame. The sealing member is removably fixed to one contact portion on either the frame or the connection wall with which portion the sealing member is in contact. The other contact portion is made to be a circular sliding portion, which is projected toward the radially inside.

(57) 要約: 下部走行体側の内輪の内周面に上部旋回体に設けた旋回ピニオンが噛合するリングギアが設けられ、内輪の内側にグリースバスが形成されており、かつ上部旋回体の旋回中心位置に形成した開口内にセンタジョイントを装着し、このセンタジョイントをグリースバスのバス形成壁から延在させた連結壁に連結し、この

[続葉有]

WO 2004/033805 A1